

PRO P-28 Boxed Electrical Tape



Technical Data Sheet

Pro P-28 is an individually boxed vinyl plastic insulating tape.

Features & Benefits:

Designed for wear and tear

Good quality

Flame retardant

Cold weather resistant

Non-corrosive adhesive

Won't crack or harden even at 10°C. Stays firm and will continuously perform in environments up to 105°C

Technical Data

- ⇒ Backing: Vinyl Film
- ⇒ Adhesive: Rubber Based
- ⇒ Total Tape Thickness: 7.0 mils
- ⇒ Tensile Strength: 20 lbs. per inch
- ⇒ Elongation: 200%
- ⇒ Adhesion to steel: 11.7oz. to 14.3oz. per inch
- ⇒ Dielectric Strength: 600 volts
- ⇒ Colors: Black, Blue, Green, Brown, Yellow, Purple, Orange, Red, White, Pink and Grey
- ⇒ UL Listed 510
- ⇒ CSA Approved
- ⇒ Individually Boxed

Application:

Pro P-28 is typically used in insulating wire splices, harness wrapping and general industrial maintenance.

621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

ISO 9001 Certified



Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications. Tape should be stored in its original packaging in a cool dry area away from direct sunlight and should be used within 12 months from date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.