


FR Lightweight Double-Sided Carpet Tape



Carrier: Polyester Film

Adhesive: Differential, Proprietary Blends

Liner: White Kraft

*Other color and liner options may be available.

Specifications: Meets FAR 25.853(a), BMS5-133F Type IV, Class 1; Airbus ABD0031, Para 7.3.2 and 7.4

Standard Sizes: 2" x 60Yd (Other sizes may be available upon request)

Applications

- Carpet and non-textile flooring installation on interior floors and stairs of aircraft
- General mounting and holding

Features

- Differential Adhesive
High-peel Liner Side
Low-peel Air Side
- Antimony Trioxide, Halogen, Bromide Free
- Flame Retardant
- Lightweight Construction

Benefits

- Clean removal from most surfaces
- Aggressive bond for secure hold
- Repositionable adhesive for easy installation
- Environmentally-friendly
- Meets FAA requirements for use in aircraft
- Improved efficiency

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness*	3.9 mils	0.099 mm	ASTM D-1000
Adhesion to Steel (Adhesive 1)	7.88 lb/in	13.80 N/cm	ASTM 3330 Meth. B
Adhesion to Steel (Adhesive 2)	2.63 lb/in	4.61 N/cm	ASTM 3330 Meth. B
Adhesion to AL (Adhesive 1)	7.81 lb/in	13.68 N/cm	ASTM 3330 Meth. B
Adhesion to AL (Adhesive 2)	2.81 lb/in	4.92 N/cm	ASTM 3330 Meth. B
Tensile Strength	27 lb/in	47.28 N/cm	ASTM D-1000
Weight	4.5 oz/sq yd	152.6 g/m ²	ASTM D-1000

*Does not include release liner

Recommended Storage Conditions: 32-90 °F at 50% RH ± 2%

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.