

P-99 POLYESTER/FIBER PACKAGING TAPE

APPLICATION

Intended primarily **for general-purpose packaging, sealing, protecting and high-tensile splicing** applications. Especially well suited for packaging where governmental specifications are involved, and with difficult-to-splice materials - coated wallcovering papers and cloths, and polyurethane-coated fabrics. An attractive, semi-translucent tape.

FEATURES AND BENEFITS

- Excellent quick-stick and high-hold characteristics.
- Moisture and abrasion resistant.
- Provides the plus-strength of polyester film.
- Will not conceal surface printing when burnished.
- Government specifications A-A-1985, L-T-99C, and PPP-T-60B.

TECHNICAL DATA

Backing material	Polyester film/paper fiber
Adhesive	Synthetic rubber/resin
Color	Natural Tan
Total tape thickness	5.5 mils/0.140 mm
Adhesion to steel	52 oz. per in./502 gm per cm
Adhesion to backing	15 oz. per in./168 gm per cm
Tensile strength	42 lbs. per in./7.14 kg per cm
Elongation	5%
Unwind @ 150 FPM	10 oz. per in./112 gm per cm
20° Hold to chrome	Permanent
Hold to boxboard	Permanent
Boxboard wetting	Delaminates boxboard
Burst strength	60 psi/42,186 kg per sq. m
Water penetration rate	2.8 gms/100 sq. in./24 hrs.
Gov't specification	A-A-1985, L-T-99C, PPP-T-60B

Note: The above are typical values and should not be used in writing specifications.

STOCK SIZES

Refer to current Industrial Division Price List.

For Additional Information on this Product, Call Toll-Free 1-800-755-TAPE.